PRODUCT SPECIFICATIONS

Construction:
- Aluminum Housing With Flush Mount Base & Vandal-Resistant Screws
- Round Dome Top With Internal Louvers
- Internal Ballast Tray For Easy Maintenance
- Bollards Can be Cut To Custom Lengths Upon Request
- Bronze Textured Powdercoat Finish
- Mounting Kit With 8” Anchor Bolts Included
- Clear Polycarbonate Vandal-Resistant Lens
- Wide Beam Spread

Light Source:
- LED 15 Watts
- 4000°K 733 Lumens Or 5000°K 763 Lumens
- Dimmable Driver
- 120-277v

Notes:
- Listed For Wet Locations
- IP65 Sealed LED Compartment
- Operating Temperatures -40°C To +40°C
- 90 Minute Emergency Battery Backup Option

JOB NAME:	
TYPE:	

Height: 42 ¼”
Diameter: 7”

Ordering Information

Example: SL-BRD-15LED-40K

SL-BRD	15LED	-	120-277	BRZ	-

SERIES	WATTAGE	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
SL-BRD	15 LED	40K-4000K 733 Lumens 50K-5000K 763 Lumens	120-277	BRZ- Bronze	EM- 90 Minute Emergency Battery Backup SF-Single Fuse DF-Double Fuse SP-Surge Protection

425 North Fox Street San Fernando, CA 91340
(818) 365-8900 FAX (818) 365-2519
www.southlandlighting.net

SOUTHLAND LIGHTING