

PRODUCT SPECIFICATIONS

Construction:

- IP65 Wet Location Rating
- Silicon Perimeter Gasket
- Snap Together Components
- Unbreakable 100% UV Stabilized Polycarbonate Lens And Body
- Aluminum Heat Sink For Superior Heat Dissipation
- Isolated LED Driver
- Hinged Gear Tray For Easy Installation
- Stainless Steel Clips


Light Source:

- 40 Watts LED With 4000 Lumens
- 5000K +80CRI
- Epistar 2835 LED Chips
- 100-277V AC Multi-Volt
- For Use In Wet Locations Between -22°F To 122°F (-30°C To 50°C)

Notes:

- Wall Or Ceiling Mount
- 5 Year Warranty
- 0-10V Dimming Standard
- 90 Minute Emergency Battery Backup Option
- Motion Sensor Option

JOB NAME:	
TYPE:	



Width: 48"
Height: 3"
Extension: 4 3/4"

Ordering Information

Example: SL-VPLED440-D

SL-VP	LED440	48"	D		
--------------	---------------	------------	----------	--	--

SERIES	WATTAGE	SIZE	Dimming	Emergency	Options
SL-VP	LED440- 40 Watts LED 4000 Lumens	48"	D- 0-10V Dimming	EM- 90 Minute Emergency Battery Backup	MS- Microwave Sensor



425 North Fox Street San Fernando, CA 91340
(818) 365-8900 FAX (818) 365-2519
www.southlandlighting.net

