PRODUCT SPECIFICATIONS

JOB NAME:	
TYPE:	

Construction:

- IP66 UL Approved Wet Location Rating
- Silicon Perimeter Gasket
- Snap Together Components
- Unbreakable 100% UV Stabilized Polycarbonate Lens And Body
- Aluminum Heat Sink For Superior Heat Dissipation
- Hinged Gear Tray For Easy Installation
- Stainless Steel Clips

Light Source:

- 40 Watts LED With 5200 Lumens
- 5000K 82CRI
- Epistar 2835 LED Chips
- 120-277VAC Multi-Volt
- For Use In Wet Locations Between -22°F To 122°F (-30°C To 50°C) UL Approved

Notes:

- Wall Or Ceiling Mount
- 0-10V Dimming Standard
- 90 Minute Emergency Battery Backup Option
- Motion Sensor Option



Width: 47 ¼”
Height: 3 ½”
Extension: 4 ½”

Ordering Information

Example: SL-VPLED440-D

SL-VP	**LED440**	**48”**	**D**	**-**	**-**

SERIES	WATTAGE	SIZE	Dimming	Emergency	Options
SL-VP	LED440- 40 Watts LED 5200 Lumens	48”	D- 0-10V Dimming	EM- 90 Minute Emergency Battery Backup	MS- Microwave Sensor

425 North Fox Street San Fernando, CA 91340
(818) 365-8900
www.southlandlighting.net

SOUTHLAND LIGHTING