

**PRODUCT SPECIFICATIONS**

**Construction:**

- IP66 Wet Location Rating
- Silicon Perimeter Gasket
- Snap Together Components
- Unbreakable 100% UV Stabilized Polycarbonate Lens And Body
- Aluminum Heat Sink For Superior Heat Dissipation
- Hinged Gear Tray For Easy Installation
- Stainless Steel Clips


**Light Source:**

- 40 Watts LED With 5200 Lumens
- 5000K 82CRI
- Epistar 2835 LED Chips
- 120-277VAC Multi-Volt
- For Use In Wet Locations Between -22°F To 122°F (-30°C To 50°C)

**Notes:**

- Wall Or Ceiling Mount
- 0-10V Dimming Standard
- 90 Minute Emergency Battery Backup Option
- Motion Sensor Option

JOB NAME:	
TYPE:	



**Width:** 47 1/4"  
**Height:** 3 1/2"  
**Extension:** 4 1/2"

**Ordering Information**

Example: SL-VPLED440-D

<b>SL-VP</b>	<b>LED440</b>	<b>48"</b>	<b>D</b>		
--------------	---------------	------------	----------	--	--

SERIES	WATTAGE	SIZE	Dimming	Emergency	Options
--------	---------	------	---------	-----------	---------

SL-VP	LED440- 40 Watts LED 5200 Lumens	48"	D- 0-10V Dimming	EM- 90 Minute Emergency Battery Backup	MS- Microwave Sensor
-------	-------------------------------------	-----	---------------------	--	-------------------------



425 North Fox Street San Fernando, CA 91340  
(818) 365-8900  
www.southlandlighting.net

